

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No. GBI P73-1

Unique identification code of the product-type:

**MB 2K
3014**

Intended use/es:

**Liquid applied water impermeable product for external installations on walls and floors,
beneath ceramic tiling
(bonded with Remmers FL Fix C2 adhesives in accordance with EN 12004)**

Manufacturer:

**REMMERS GmbH
Bernhard-Remmers-Straße 13
D-49624 Lönningen
Fon. 0049 / 5432 / 83- 0**

System/s of AVCP:

System 3

Harmonised standard:

EN 14891: 2012 + AC: 2012

Notified body/ies:

The notified body
The logo for the notified body, featuring the text "iBMB" in red and "MPA" in large black letters, with "TU BRAUNSCHWEIG" in smaller black letters below it.
**Materialprüfanstalt (MPA) Braunschweig
Beethovenstr. 52
D-38106 Braunschweig
Identification no. 0761,**

performed the determination of the product-type on the basis of type testing and issued:
 test report no. P-1201/551/18
 test report no. P-1201/552/18
 test report no. P-1201/553/18
 test report no. P-1201/554/18
 test report no. P-1202/361/19

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	System 3	EN 14891:2012 + AC: 2012
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$		
Waterproofing	no penetration		
Crack bridging ability	$\geq 0,75 \text{ mm}$		
Crack bridging ability at low temperature	$\geq 0,75 \text{ mm}$ at $-5 \text{ }^\circ\text{C}$		
Release of dangerous substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Remmers GmbH
Dr. Christiane Saalbach, Bereichsleiterin F&E - mineralische Baustoffe

Löningen, 16.04.2020
 (place an date of issue)


 (signature)