

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No. **GBI P77-1**

Unique identification code of the product-type:

**WP Flex 1K
0445**

Intended use/es:

**Liquid applied water impermeable product on walls and floors,
beneath ceramic tiling
(bonded with Remmers FL fix C2 adhesives in accordance with EN 12004)**

Manufacturer:

**REMMERS GmbH
Bernhard-Remmers-Straße 13
D-49624 Lönigen
Tel. 0049 / 5432 / 83- 0**

System/s of AVCP:

System 3

Harmonised standard:

EN 14891: 2012 + AC: 2012

Notified body/ies:

The notified body
The logo for iBMB MPA, with "iBMB" in red and "MPA" in black, with "TU BRAUNSCHWEIG" in smaller black text below it.
**Materialprüfanstalt (MPA) Braunschweig
Beethovenstr. 52
D-38106 Braunschweig
Identification number 0761**

has conducted the type testing of the product and the following is displayed:

Prüfbericht – Nr. 1202 / 364 / 19

Prüfbericht – Nr. 1202 / 365 / 19

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	System 3	EN 14891:2012 + AC: 2012
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with chlorine water	$\geq 0,5 \text{ N/mm}^2$		
Waterproofing	no penetration		
Crack bridging ability	$\geq 0,75 \text{ mm}$		
Crack bridging ability at low temperature (at $-5 \text{ }^\circ\text{C}$)	$\geq 0,75 \text{ mm}$		
Release of dangerous substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Christiane Saalbach, Bereichsleiterin F&E Bautenschutz

Löningen, 10.01.2020

(place an date of issue)



(signature)