

Acolan[®] CERAMIX



Article No. 6631-6669

Blinding material for coloured anti-slip covers.

Properties:

Special, wear resistant, coloured blinding material

Range of use:

To be used as blinding material for anti-slip covers and for the production of mortars and screed mixtures.

Colours/grain sizes:

Colours as per Ceramix Colour Card

Ceramix 03 : Art. Nr. 6669
Ceramix 07 : Art. Nr. 6659
Ceramix 12: Art. Nr. 6649

Special grain sizes: Art. Nr. 1251

Specifications:

Form: solid
Odour: odourless
Colour: coloured
Density: 2.65 g/cm³

Working instructions:

Spread the material full cover into the fresh base coat. After hardening, remove unbound excess of Acolan Ceramix. When used as filling material for mortars, first mix components A and B of the binder, e.g. Viscacid FM Decor, thoroughly and add the filling material. When mixing larger quantities, it is recommended to use a compulsory mixer.

Packaging, application rate and storage:

Packaging: 25 kg bags

Application rate: depending on the kind of use

Shelf-life: Unlimited if stored dry.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques. Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet.

Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid.

With the publication of this Technical Information Sheet all previous editions are no longer valid.