

# Tor QD Thinner

TH19

## intended uses

For the thinning (where necessary) of Tor Quick Drying Machinery Primers and Finishes and for the cleaning of the same materials from application equipment. Can also be used for degreasing metal components prior to painting.

## product description

Xylene (mixed isomers)

## product information

<b>Product reference</b>	TH19
<b>Volume solids</b>	Nil
<b>Typical thickness</b>	N/A
<b>Theoretical coverage</b>	N/A
<b>Practical coverage</b>	N/A
<b>Appearance/Colour range</b>	N/A
<b>VOC content</b>	866 gms/litre

## application details

<b>Mix ratio</b>	N/A
<b>Method of application</b>	N/A
<b>Thinner</b>	N/A
<b>Cleaner</b>	N/A
<b>Pot Life</b>	N/A
<b>Drying time</b>	N/A

Substrate Temperature	Touch Dry	Hard Dry	Overcoating Interval	
			Minimum	Maximum
20°C				

**Note:** Drying/curing times will be shortened by higher temperatures and lengthened by lower temperatures

## storage and handling

**Storage** Store the closed containers in a store room which is either in a safe place or is a fire resisting structure. The storage and conditions must meet the statutory requirements of The Highly Flammable Liquids and Petroleum Gases Regulations 1972.

<b>Pack Size</b>	5 litres, 25 litres and 205 litres
<b>Flash point</b>	23°C
<b>Product weight</b>	0.866 kilos/litre
<b>Shelf life</b>	2 years in unopened containers

## surface preparation

N/A

## limitations

Must be stored in accordance with the statutory requirements of The Highly Flammable Liquids and Petroleum Gases Regulations 1972.

Special paints usually require special thinners.

## safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

## definitions

### **Tolerances**

All information quoted in this data sheet is subject to normal manufacturing tolerances.

### **Practical coverage**

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

### **Pot Life**

Applies only to two component products and refers to the time the mixture remains usable.

## disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

Updated: August 1999  
TH19