

# watco® SAFETY DATA SHEET

Chemi-Coat - Curing Agent

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Chemi-Coat - Curing Agent  
**Product description** : Floorcoating.  
**Product type** : Liquid.  
**UFI** : J4E0-A08F-V00W-MUDE

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses                                    |        |
|--|--------|
| Professional use<br>Consumer use<br>Industrial use |        |
| Uses advised against                               | Reason |
| None identified.                                   | -      |

### 1.3 Details of the supplier of the safety data sheet

Watco UK Limited  
Eastgate Court  
195-205 High Street  
Guildford  
Surrey  
GU1 3EH  
Telephone no.: +44 (0) 1483 425000 (08:00 - 18:00)  
Fax no.: +44 (0) 1483 428888  
**e-mail address of person responsible for this SDS** : rpmeurohas@rustoleum.eu

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number United Kingdom: : 809 2166  
Northern Ireland : Available 8am to 10pm 7 days per week

#### Supplier

Telephone number United Kingdom: : +353 19014670  
Northern Ireland  
Hours of operation : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

## SECTION 2: Hazards identification

Acute Tox. 4, H302  
 Skin Corr. 1B, H314  
 Eye Dam. 1, H318  
 Skin Sens. 1, H317  
 STOT RE 2, H373  
 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### Hazard pictograms



#### Signal word

: Danger

#### Hazard statements

: H302 - Harmful if swallowed.  
 H314 - Causes severe skin burns and eye damage.  
 H317 - May cause an allergic skin reaction.  
 H373 - May cause damage to organs through prolonged or repeated exposure.  
 H411 - Toxic to aquatic life with long lasting effects.

#### Precautionary statements

##### General

: P103 - Read carefully and follow all instructions.  
 P102 - Keep out of reach of children.  
 P101 - If medical advice is needed, have product container or label at hand.

##### Prevention

: P280 - Wear protective gloves, protective clothing and eye or face protection.  
 P273 - Avoid release to the environment.  
 P260 - Do not breathe vapour.

##### Response

: P391 - Collect spillage.  
 P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.  
 P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor.  
 P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

##### Storage

: P405 - Store locked up.

##### Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### Hazardous ingredients

: Formaldehyde, polymer with benzenamine, hydrogenated  
 2,4,6-tris(dimethylaminomethyl)phenol  
 m-fenilenbis(methylamine)  
 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-  
 2,3-epoxypropane, reaction products with ethylenediamine  
 bis[(dimethylamino)methyl]phenol

#### Supplemental label elements

: Not applicable.

#### Supplemental label elements : Detergents - Regulation (EC) No 907/2006

: Not applicable.

Chemi-Coat - Curing Agent

## SECTION 2: Hazards identification

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Yes, applicable.

**Tactile warning of danger** : Yes, applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

**United Kingdom: Northern Ireland**

| Product/ingredient name   | Identifiers  | %         | Classification   | Specific Conc. Limits, M-factors and ATEs                                  | Type |
|---|--|-----------|--|--|------|
| benzyl alcohol  | REACH #: 01-2119492630-38<br>EC: 202-859-9<br>CAS: 100-51-6<br>Index: 603-057-00-5 | ≥25 - ≤50 | Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>Eye Irrit. 2, H319   | ATE [Oral] = 1620 mg/kg<br>ATE [Inhalation (dusts and mists)] = 4,178 mg/l | [1]  |
| Formaldehyde, polymer with benzenamine, hydrogenated                                    | CAS: 135108-88-2<br>List #: 603-894-6  | ≥10 - ≤25 | Acute Tox. 3, H301<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT RE 2, H373<br>Aquatic Chronic 3, H412    | ATE [Oral] = 100 mg/kg   | [1]  |
| Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis (methylamine) | EC: 500-137-0<br>CAS: 57214-10-5   | ≥10 - ≤25 | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   | M [Acute] = 1<br>M [Chronic] = 1   | [1]  |
| 2,4,6-tris (dimethylaminomethyl) phenol   | EC: 202-013-9<br>CAS: 90-72-2  | ≤10       | Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317   | -  | [1]  |
| m-fenilenbis(methylamine)   | REACH #: 01-2119480150-50<br>EC: 216-032-5<br>CAS: 1477-55-0<br>Index: 216-032-5   | ≤10       | Acute Tox. 4, H302<br>Acute Tox. 4, H332<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Chronic 3, H412 | ATE [Oral] = 930 mg/kg<br>ATE [Inhalation (gases)] = 4500 ppm              | [1]  |
| 4,4'-Isopropylidenediphenol,  | REACH #:   | ≤5        | Acute Tox. 4, H302   | ATE [Oral] = 500   | [1]  |

Chemi-Coat - Curing Agent

### SECTION 3: Composition/information on ingredients

|   |  |    |   |   |     |
|---|--|----|---|---|-----|
| oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with ethylenediamine | 01-2120766318-46<br>EC: 500-253-1<br>CAS: 72480-18-3             |    | Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410  | mg/kg<br>M [Acute] = 1<br>M [Chronic] = 1 |     |
| bis[(dimethylamino)methyl]phenol  | REACH #:<br>01-2119560597-27<br>EC: 275-162-0<br>CAS: 71074-89-0 | ≤3 | Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1B, H317  | -   | [1] |
| salicylic acid  | REACH #:<br>01-2119486984-17<br>EC: 200-712-3<br>CAS: 69-72-7    | ≤1 | Acute Tox. 4, H302<br>Eye Dam. 1, H318<br>Repr. 2, H361d<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | ATE [Oral] = 891 mg/kg                    | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Type

[1] Substance classified with a health or environmental hazard

List numbers have no legal significance.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person.

## SECTION 4: First aid measures

If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
halogenated compounds

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## SECTION 7: Handling and storage

### Seveso Directive - Reporting thresholds

#### Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| E2       | 200 tonne                       | 500 tonne               |

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

| Product/ingredient name | Type | Exposure              | Value                   | Population                     | Effects  |
|-------------------------|------|-----------------------|-------------------------|--------------------------------|----------|
| benzyl alcohol          | DNEL | Short term Dermal     | 47 mg/kg bw/day         | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 450 mg/m <sup>3</sup>   | Workers                        | Systemic |
|                         | DNEL | Long term Dermal      | 9,5 mg/kg bw/day        | Workers                        | Systemic |
|                         | DNEL | Long term Inhalation  | 90 mg/m <sup>3</sup>    | Workers                        | Systemic |
|                         | DNEL | Short term Dermal     | 28,5 mg/kg bw/day       | General population [Consumers] | Systemic |
|                         | DNEL | Short term Inhalation | 40,55 mg/m <sup>3</sup> | General population [Consumers] | Systemic |
|                         | DNEL | Short term Oral       | 25 mg/kg bw/day         | General population [Consumers] | Systemic |
|                         | DNEL | Long term Dermal      | 5,7 mg/kg bw/day        | General population [Consumers] | Systemic |
|                         | DNEL | Long term Inhalation  | 8,11 mg/m <sup>3</sup>  | General population [Consumers] | Systemic |
|                         | DNEL | Long term Oral        | 5 mg/kg                 | General                        | Systemic |

**SECTION 8: Exposure controls/personal protection**

|  |      |                       |                        |                        |          |
|--|------|-----------------------|------------------------|------------------------|----------|
|  |      |                       | bw/day                 | population [Consumers] |          |
|  | DNEL | Short term Dermal     | 20 mg/kg               | General population     | Systemic |
|  | DNEL | Long term Oral        | 4 mg/kg                | General population     | Systemic |
|  | DNEL | Long term Dermal      | 8 mg/kg                | Workers                | Systemic |
|  | DNEL | Short term Oral       | 20 mg/kg               | General population     | Systemic |
|  | DNEL | Long term Dermal      | 4 mg/kg                | General population     | Systemic |
|  | DNEL | Short term Inhalation | 27 mg/m <sup>3</sup>   | General population     | Systemic |
|  | DNEL | Long term Inhalation  | 5,4 mg/m <sup>3</sup>  | General population     | Systemic |
|  | DNEL | Long term Inhalation  | 22 mg/m <sup>3</sup>   | Workers                | Systemic |
|  | DNEL | Short term Inhalation | 110 mg/m <sup>3</sup>  | Workers                | Systemic |
|  | DNEL | Short term Dermal     | 40 mg/kg               | Workers                | Systemic |
|  | DNEL | Long term Dermal      | 2 mg/kg                | Workers                | Systemic |
| Formaldehyde, polymer with benzenamine, hydrogenated | DNEL | Short term Inhalation | 2 mg/m <sup>3</sup>    | Workers                | Systemic |
|  | DNEL | Long term Inhalation  | 0,2 mg/m <sup>3</sup>  | Workers                | Systemic |
|  | DNEL | Short term Dermal     | 6 mg/kg                | Workers                | Systemic |
| 2,4,6-tris(dimethylaminomethyl) phenol               | DNEL | Long term Inhalation  | 0,31 mg/m <sup>3</sup> | Workers                | Systemic |
| salicylic acid                                       | DNEL | Long term Inhalation  | 5 mg/m <sup>3</sup>    | Workers                | Systemic |
|  | DNEL | Short term Oral       | 4 mg/kg                | General population     | Systemic |
|  | DNEL | Long term Dermal      | 1 mg/kg                | General population     | Systemic |
|  | DNEL | Long term Oral        | 1 mg/kg                | General population     | Systemic |
|  | DNEL | Long term Dermal      | 2,3 mg/kg              | Workers                | Systemic |
|  | DNEL | Long term Inhalation  | 4 mg/m <sup>3</sup>    | General population     | Systemic |
|  | DNEL | Long term Inhalation  | 5 mg/m <sup>3</sup>    | Workers                | Local    |

**PNECs**

| Product/ingredient name | Compartment Detail                                   | Value       | Method Detail      |
|-------------------------|--|-------------|--------------------|
| benzyl alcohol          | Fresh water  | 1 mg/l      | Assessment Factors |
|                         | Marine   | 0,1 mg/l    | Assessment Factors |
|                         | Fresh water sediment                                 | 5,27 mg/kg  | Assessment Factors |
|                         | Marine water sediment                                | 0,527 mg/kg | Assessment Factors |
|                         | Soil   | 0,456 mg/kg | Assessment Factors |
|                         | Sewage Treatment Plant                               | 39 mg/l     | Assessment Factors |
|                         | Fresh water  | 2,3 mg/l    | -                  |
|                         | Sewage Treatment Plant                               | 39 mg/l     | -                  |
|                         | Fresh water sediment                                 | 5,27 mg/kg  | -                  |
|                         | Soil   | 0,456 mg/kg | -                  |
|                         | Marine water sediment                                | 0,527 mg/kg | -                  |
|                         | Fresh water  | 1 mg/l      | -                  |
|                         | Marine water   | 0,1 mg/l    | -                  |
|                         | Formaldehyde, polymer with benzenamine, hydrogenated | Fresh water | 0,015 mg/l         |



## SECTION 8: Exposure controls/personal protection

|   |                        |             |   |
|---|------------------------|-------------|---|
| 2,4,6-tris(dimethylaminomethyl)phenol<br>salicylic acid | Marine water sediment  | 1,5 mg/kg   | - |
|   | Fresh water sediment   | 15 mg/kg    | - |
|   | Marine water           | 0,002 mg/l  | - |
|   | Sewage Treatment Plant | 1,9 mg/l    | - |
|   | Soil                   | 1,8 mg/kg   | - |
|   | Fresh water            | 0,84 mg/l   | - |
|   | Fresh water sediment   | 1,42 mg/kg  | - |
|   | Marine water sediment  | 0,142 mg/kg | - |
|   | Fresh water            | 0,2 mg/l    | - |
|   | Marine water           | 0,02 mg/l   | - |
|   | Sewage Treatment Plant | 162 mg/l    | - |
|   | Soil                   | 0,166 mg/kg | - |

### 8.2 Exposure controls

**Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Recommended: safety glasses with side-shields.

#### Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber or butyl rubber (0.6 mm) gloves

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

## SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 141)
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

- Physical state** : Liquid.
- Colour** : Not available.
- Odour** : Not available.
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not relevant due to nature of the product.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosion limit** : Not available.
- Flash point** : Closed cup: >60°C (>140°F)
- Auto-ignition temperature** : Not relevant due to nature of the product.
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- pH : Justification** : Product is non-soluble (in water).
- Viscosity** : Not available.
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Miscible with water** : No.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

| Ingredient name | Vapour Pressure at 20°C |        |        | Vapour pressure at 50°C |     |        |
|-----------------|-------------------------|--------|--------|-------------------------|-----|--------|
|                 | mm Hg                   | kPa    | Method | mm Hg                   | kPa | Method |
| benzyl alcohol  | 0,05                    | 0,0067 |        |                         |     |        |

- Evaporation rate** : Not available.
- Relative density** : 1,05 to 1,1

Chemi-Coat - Curing Agent

## SECTION 9: Physical and chemical properties

|                                 |   |
|---------------------------------|---|
| <b>Density</b>                  | : 1,05 to 1,1 g/cm <sup>3</sup> [20°C (68°F)] [DIN 53217] |
| <b>Vapour density</b>           | : Not available.  |
| <b>Explosive properties</b>     | : Not available.  |
| <b>Oxidising properties</b>     | : Not available.  |
| <b>Particle characteristics</b> |   |
| <b>Median particle size</b>     | : Not applicable.   |

## SECTION 10: Stability and reactivity

|  |  |
|--|--|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| <b>10.2 Chemical stability</b>                 | : The product is stable.   |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| <b>10.4 Conditions to avoid</b>                | : No specific data.  |
| <b>10.5 Incompatible materials</b>             | : No specific data.  |
| <b>10.6 Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

| Product/ingredient name  | Result                          | Species | Dose                 | Exposure |
|--|---------------------------------|---------|----------------------|----------|
| benzyl alcohol   | LC50 Inhalation Dusts and mists | Rat     | 4,178 mg/l           | 4 hours  |
|  | LD50 Dermal                     | Rabbit  | 2000 mg/kg           | -        |
|  | LD50 Oral                       | Rat     | 1620 mg/kg           | -        |
| 2,4,6-tris(dimethylaminomethyl)phenol  | LD50 Oral                       | Rat     | 1660 mg/kg           | -        |
|  | LD50 Dermal                     | Rabbit  | 1242 mg/kg           | -        |
|  | LD50 Oral                       | Rat     | 1673 mg/kg           | -        |
| m-fenilenbis(methylamine)  | LC50 Inhalation Dusts and mists | Rat     | 1,34 mg/l            | 4 hours  |
|  | LC50 Inhalation Gas.            | Rat     | 700 ppm              | 1 hours  |
|  | LD50 Dermal                     | Rabbit  | 2 g/kg               | -        |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with ethylenediamine | LD50 Oral                       | Rat     | 930 mg/kg            | -        |
|  | LD50 Oral                       | Rabbit  | 300 to 2000 mg/kg    | -        |
|  | LD50 Oral                       | Rabbit  | 300 to 2000 mg/kg    | -        |
| salicylic acid   | LC50 Inhalation Dusts and mists | Rat     | 0,9 g/m <sup>3</sup> | 4 hours  |
|  | LD50 Oral                       | Rat     | 891 mg/kg            | -        |

**Conclusion/Summary** : Harmful if swallowed.

#### Acute toxicity estimates

Chemi-Coat - Curing Agent

## SECTION 11: Toxicological information

| Product/ingredient name  | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| Chemi-Coat - Curing Agent  | 500          | N/A            | N/A                      | N/A                         | N/A                                 |
| benzyl alcohol   | 1620         | N/A            | N/A                      | N/A                         | 4,178                               |
| Formaldehyde, polymer with benzenamine, hydrogenated   | 100          | N/A            | N/A                      | N/A                         | N/A                                 |
| m-fenilenbis(methylamine)  | 930          | N/A            | 4500                     | N/A                         | 1,34                                |
| 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with ethylenediamine | 500          | N/A            | N/A                      | N/A                         | N/A                                 |
| salicylic acid   | 891          | N/A            | N/A                      | N/A                         | N/A                                 |

### Irritation/Corrosion

| Product/ingredient name                 | Result                   | Species | Score | Exposure                | Observation |
|---|--------------------------|---------|-------|-------------------------|-------------|
| benzyl alcohol                          | Eyes - Irritant          | Rabbit  | -     | -                       | -           |
|   | Skin - Moderate irritant | Pig     | -     | 100 Percent             | -           |
| 2,4,6-tris (dimethylaminomethyl) phenol | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 50 Micrograms  | -           |
|   | Skin - Mild irritant     | Rat     | -     | 0.025 Milliliters       | -           |
|   | Skin - Severe irritant   | Rabbit  | -     | 24 hours 2 milligrams   | -           |
| m-fenilenbis(methylamine)               | Skin - Severe irritant   | Rat     | -     | 0.25 Milliliters        | -           |
|   | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 50 Micrograms  | -           |
|   | Skin - Severe irritant   | Rabbit  | -     | 24 hours 750 Micrograms | -           |

### Conclusion/Summary

- Skin** : Causes severe skin burns and eye damage.
- Eyes** : Causes serious eye damage.
- Respiratory** : May cause damage to organs through prolonged or repeated exposure if inhaled.

### Sensitisation

| Product/ingredient name                 | Route of exposure | Species    | Result          |
|---|-------------------|------------|-----------------|
| 2,4,6-tris (dimethylaminomethyl) phenol | skin              | Guinea pig | Not sensitizing |

### Conclusion/Summary

- Skin** : May cause an allergic skin reaction.
- Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

| Product/ingredient name | Result               | Species | Dose | Exposure                   |
|-------------------------|----------------------|---------|------|----------------------------|
| benzyl alcohol          | Negative - Oral - TD | Rat     | -    | 103 weeks; 5 days per week |

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

Chemi-Coat - Curing Agent

## SECTION 11: Toxicological information

| Product/ingredient name  | Maternal toxicity | Fertility | Developmental toxin | Species | Dose           | Exposure |
|--|-------------------|-----------|---------------------|---------|----------------|----------|
| Formaldehyde, polymer with benzenamine, hydrogenated 2,4,6-tris (dimethylaminomethyl) phenol | -                 | -         | -                   | Rat     | Oral: 15 mg/kg | 28 days  |
|  | -                 | -         | Negative            | Rat     | Oral           | 28 days  |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

| Product/ingredient name | Result                                  | Species        | Dose      | Exposure |
|-------------------------|---|----------------|-----------|----------|
| benzyl alcohol          | Negative - Route of exposure unreported | Mouse - Female | 550 mg/kg | -        |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name                              | Category   | Route of exposure | Target organs |
|--|------------|-------------------|---------------|
| Chemi-Coat - Curing Agent                            | Category 2 | -                 | -             |
| Formaldehyde, polymer with benzenamine, hydrogenated | Category 2 | -                 | -             |

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes severe burns. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

## SECTION 11: Toxicological information

### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Reproductive toxicity** : No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

| Product/ingredient name   | Result                             | Species  | Exposure |
|---|------------------------------------|--|----------|
| benzyl alcohol  | Acute EC50 770 mg/l                | Algae  | 72 hours |
|   | Acute LC50 646 mg/l                | Fish - Leuciscus idus  | 48 hours |
|   | Acute LC50 460000 µg/l Fresh water | Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis (methylamine) | Acute NOEC 310 mg/l                | Algae  | 72 hours |
|   | Acute LC50 0,5 to 1 mg/l           | Fish   | 96 hours |
| 2,4,6-tris (dimethylaminomethyl) phenol   | Acute EC50 84 mg/l                 | Algae  | 72 hours |
|   | Acute LC50 180 to 240 mg/l         | Fish   | 96 hours |
| m-fenilenbis(methylamine)   | Acute LC50 175 mg/l                | Fish - Cyprinus carpio   | 96 hours |
|   | Acute EC50 10 to 100 mg/l          | Daphnia spec.  | 48 hours |
| salicylic acid  | Acute LC50 >100 mg/l               | Fish   | 96 hours |
|   | Acute EC50 213,9 mg/l              | Crustaceans - Photobacterium Phosphoreum                               | 24 hours |
|   | Acute EC50 105 mg/l                | Daphnia spec.  | 48 hours |
|   | Acute LC50 90 mg/l                 | Fish   | 48 hours |
|   | Chronic NOEC 5,6 mg/l Fresh water  | Daphnia spec. - Daphnia magna - Neonate                                | 21 days  |

**Conclusion/Summary** : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Chemi-Coat - Curing Agent

## SECTION 12: Ecological information

| Product/ingredient name             | Test      | Result                      | Dose                        | Inoculum |
|-------------------------------------|-----------|-----------------------------|-----------------------------|----------|
| benzyl alcohol                      | OECD 301A | 96 % - Readily - 21 days    | -                           | -        |
| 2,4,6-tris<br>(dimethylaminomethyl) | OECD 301D | 4 % - Not readily - 28 days | -                           | -        |
| phenol                              |           |                             |                             |          |
| salicylic acid                      | OECD 301C | 88,1 % - Readily - 14 days  | 0,95 qO <sub>2</sub> /g DOC | -        |

**Conclusion/Summary** : Based on available data, the classification criteria are not met. This product has not been tested for biodegradation.

| Product/ingredient name             | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------------------|-------------------|------------|------------------|
| benzyl alcohol                      | -                 | -          | Readily          |
| 2,4,6-tris<br>(dimethylaminomethyl) | -                 | -          | Not readily      |
| phenol                              |                   |            |                  |
| salicylic acid                      | -                 | -          | Readily          |

### 12.3 Bioaccumulative potential

| Product/ingredient name             | LogP <sub>ow</sub> | BCF  | Potential |
|-------------------------------------|--------------------|------|-----------|
| benzyl alcohol                      | 0,87               | -    | low       |
| 2,4,6-tris<br>(dimethylaminomethyl) | 0,219              | -    | low       |
| phenol                              |                    |      |           |
| m-fenilenbis(methylamine)           | 0,18               | 2,69 | low       |
| salicylic acid                      | 2.21 to 2.26       | -    | low       |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.








## SECTION 13: Disposal considerations

### European waste catalogue (EWC)

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID  | ADN  | IMDG  | IATA   |
|--|--|--|---|--|
| <b>14.1 UN number or ID number</b>     | UN2735   | UN2735   | UN2735  | UN2735   |
| <b>14.2 UN proper shipping name</b>    | Amines, liquid, corrosive, N.O.S. (m-fenilenbis (methylamine))   | Amines, liquid, corrosive, N.O.S. (m-fenilenbis (methylamine))   | Amines, liquid, corrosive, N.O.S. (m-fenilenbis (methylamine)).<br>Marine pollutant (Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis (methylamine))   | Amines, liquid, corrosive, N.O.S. (m-fenilenbis (methylamine))   |
| <b>14.3 Transport hazard class(es)</b> | 8<br>  | 8<br>  | 8<br>  | 8<br>   |
| <b>14.4 Packing group</b>              | III  | III  | III   | III  |
| <b>14.5 Environmental hazards</b>      | Yes.   | Yes.   | Yes.  | Yes. The environmentally hazardous substance mark is not required.   |
| <b>Additional information</b>          | The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.<br><b>Tunnel code</b> (D/E)   | The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.   | The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.<br><b>Emergency schedules</b> F-A; S-B  | The environmentally hazardous substance mark may appear if required by other transportation regulations.<br><b>Quantity limitation</b><br>Passenger and Cargo Aircraft: 5 L.<br>Packaging instructions: 852.<br>Cargo Aircraft Only: 60 L. Packaging instructions: 856.<br>Limited Quantities - Passenger Aircraft: 1 L. Packaging instructions: Y841. |



Chemi-Coat - Curing Agent

## SECTION 14: Transport information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**EU Regulation (EC) No. 1907/2006 (REACH)**

### Annex XIV - List of substances subject to authorisation

#### Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Other EU regulations

**VOC for Ready-for-Use Mixture** : IIA/j. Two-pack reactive performance coatings for specific end use such as floors. EU limit value for this product : 500g/l (2010.) This product contains a maximum of 50 g/l VOC.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

### Ozone depleting substances (1005/2009/EC)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

### Persistent Organic Pollutants (850/2004/EC)

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

Category

E2

### National regulations

United Kingdom: Northern Ireland

Chemi-Coat - Curing Agent

## SECTION 15: Regulatory information

**References** : EH40/2005 Workplace exposure limits  
 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878  
 REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

### International regulations

#### Stockholm Convention on Persistent Organic Pollutants

| List name   | Ingredient name | Status |
|-------------|-----------------|--------|
| Not listed. |                 |        |

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

| List name   | Ingredient name | Status |
|-------------|-----------------|--------|
| Not listed. |                 |        |

**CN code** : 3209 90 00 00

### Inventory list

**Australia** : All components are listed or exempted.  
**Canada** : All components are listed or exempted.  
**China** : All components are listed or exempted.  
**Eurasian Economic Union** : **Russian Federation inventory**: Not determined.  
**Japan** : **Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**New Zealand** : All components are listed or exempted.  
**Philippines** : All components are listed or exempted.  
**Republic of Korea** : All components are listed or exempted.  
**Taiwan** : At least one component is not listed.  
**Thailand** : Not determined.  
**Turkey** : Not determined.  
**United States** : All components are active or exempted.  
**Viet Nam** : Not determined.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Chemi-Coat - Curing Agent

## SECTION 16: Other information

| Classification          | Justification   |
|-------------------------|-----------------|
| Acute Tox. 4, H302      | Expert judgment |
| Skin Corr. 1B, H314     | Expert judgment |
| Eye Dam. 1, H318        | Expert judgment |
| Skin Sens. 1, H317      | Expert judgment |
| STOT RE 2, H373         | Expert judgment |
| Aquatic Chronic 2, H411 | Expert judgment |

### Full text of abbreviated H statements

**Date of printing** : 15/03/2023

**Date of issue/ Date of revision** : 15/03/2023

**Date of previous issue** : 11/08/2022

**Version** : 3.01

### Notice to reader

**IMPORTANT NOTE:** The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.