

Page 1/9

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Trade name Primer HF (Primer SV)

Article number: 6438

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Sector of Use** 

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services,

craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

**Process category** 

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

**Environmental release category** 

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC10a Widespread use of articles with low release (outdoor)

Application of the substance / the mixture Priming

Uses advised against No further relevant information available.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Postfach 1255 D-49624 Löningen / Germany

Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985

Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

#### 1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Flam. Lig. 3 H226 Flammable liquid and vapour.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Remmers (UK) Limited

Unit B1 The Fleming Centre

West Sussex RH10 9NN

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

## Trade name Primer HF (Primer SV)

(Contd. of page 1)

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### **Hazard pictograms**







GHS02 GHS07

#### Signal word Danger

#### Hazard-determining components of labelling:

isoparaffine hydrocarbon mixture hydrocarbons, C9, aromatics cumene

benzene

#### **Hazard statements**

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

#### SECTION 3: Composition/information on ingredients

#### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components:			
EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39-XXXX	isoparaffine hydrocarbon mixture Asp. Tox. 1, H304	≥60-<80%	
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	≥20-<25%	
CAS: 35435-21-3 Reg.nr.: 01-2119555666-27-XXXX	Triethoxy(2,4,4-trimethylpentyl)silane Flam. Liq. 3, H226	≥2.5-<5%	

(Contd. on page 3)

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

### Trade name Primer HF (Primer SV)

(Contd. of page 2)

#### **Additional information**

Benzene content: < 0,1% Note P is applicable. It is not necessary to classify nor to mark the product as carcinogenic.

For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General information**

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

After inhalation Seek medical treatment in case of complaints.

After skin contact If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water.

#### After swallowing

Do not induce vomiting. In case of prolonged discomfort, see a doctor. If the patient is conscious, give water to drink.

#### 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

nausea

Unconsciousness

Inhalation may have an irritating effect on mucous membranes.

Skin contact may cause irritation.

Dry skin

Eye contact may cause temporary pain.

#### Danger

Swallowing followed by vomiting may lead to aspiration into the lungs which leads to suffocation or toxic pulmonary oedema.

Long-term or repeated exposure may cause inflammation of the skin (dermatitis).

#### 4.3 Indication of any immediate medical attention and special treatment needed

In contact with water (also in the digestive tract) the product plits off methanol in larger quantities.

Therefore methanol intoxication and a respective latency period of several days must be taken into consideration.

To avoid dermatitis (skin inflammation), use skin cream.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing agents

Foam

Water spray jet

Water mist

Dry extinguishing agents, carbon dioxide, sand or earth should only be used for small fires.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

#### 5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

(in case of incomplete combustion)

Under certain fire conditions, traces of other toxic substances cannot be excluded.

Conflagration gases from organic materials are always rated toxic for breathing.

When heated above the flash point, the formation of ignition-capable mixtures is possible.

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

#### 5.3 Advice for firefighters

#### Protective equipment:

Wear full protective suit.

Wear self-contained breathing apparatus.

#### **Additional information**

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

## Trade name Primer HF (Primer SV)

(Contd. of page 3)

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Prevent from spreading (e.g. by confining or oil barrier).

Inform responsible authorities in case product reaches bodies of water or sewage system.

Inform responsible authorities in case product reaches bodies of water or sewage system.

#### 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Place leaking containers in a marked drum or recovery drum.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### 6.4 Reference to other sections

Fumes can combine with air to form an explosive mixture.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

#### Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

Requirements to be met by storerooms and containers: No special requirements.

#### Information on storage in a common storage facility:

Suitable material for containers and pipes: Light metals and their alloys.

#### Further information about storage conditions:

Store container in a well ventilated position.

Protect from humidity and keep away from water.

Do not smoke in storage areas. Storage temperature: room temperature.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

Additional information about design of technical systems: Use only in well-ventilated areas.

#### 8.1 Control parameters

#### Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

#### 8.2 Exposure controls

#### Personal protective equipment

### General protective and hygienic measures

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Wash hands before pauses and after work.

#### Respiratory equipment: Filter A/P2.

(Contd. on page 5)

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

## Trade name Primer HF (Primer SV)

(Contd. of page 4)

#### Protection of hands:

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed safety glasses.

#### **Body protection:**

If body contact is possible, wear suitable arm protection.

Avoid skin contact.

#### **SECTION 9: Physical and chemical properties**

0.4 Information on bosis abusisal and about all anomatics		
9.1 Information on basic physical and chemical properties General Information		
Appearance:		
Form:	Fluid	
Colour:	clear	
Odour:	Aromatic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Not determined	
Initial boiling point and boiling range:	Not determined	
Flash point:	> 42 °C	
Inflammability (solid, gaseous)	Not applicable.	
Ignition temperature:	not applicable	
Decomposition temperature:	Not determined.	
Self-inflammability:	Product is not self-igniting.	
Explosive properties:	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.	
Explosive Limits:		
Lower:	0.6 Vol %	
Upper:	7.0 Vol %	
Vapour pressure at 20 °C:	1 hPa	
Density at 20 °C:	0.88 g/cm <sup>3</sup>	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
Distribution coefficient (n-octanol/water): 3.7 - 4.5 log POW		
`	solvent naphtha light	

(Contd. on page 6)

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

## Trade name Primer HF (Primer SV)

(Contd. of page 5)

Viscosity: dynamic: kinematic at 20 °C:	Not determined. 11 s (DIN 53211/4)
Solvent separation test	< 3 %
Solid content: 9.2 Other information	11.0 % No further relevant information available.

### **SECTION 10: Stability and reactivity**

10.1 Reactivity No further relevant information available.

#### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

#### 10.3 Possibility of hazardous reactions

Reacts with water forming methanol.

Used empty containers may contain product gases which form explosive mixtures with air

- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: Through humidity, water and protic agents: methanol

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:			
isoparaffi	isoparaffine hydrocarbon mixture		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	

Skin corrosion/irritation: Dries skin out.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation: Based on available data, the classification criteria are not met.

#### **Experience with humans:**

After swallowing and subsequent vomiting, aspiration into the lungs may occur which leads to suffocation or toxic lung oedema.

Frequent or longer lasting skin contact may degrease and dry out skin which may lead to skin irritation and inflammation (dermatitis).

#### Additional toxicological information:

Avoid exposure inhalation!

Caution! The product may hydrolise in the gastro-intestinal tract and release methanol. According to literature, methanol (67-56-1) dries skin out, irritates mucous membranes and has a narcotic effect that can lead to coma or death. Skin resorption possible. After a delay in time, damage to heart, kidneys, liver and optic nerve (blindness) may occur.

Alkoxy silane: Do not inhale aerosol mist because of the risk of lung damage.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure:

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

#### Aspiration hazard:

May be fatal if swallowed and enters airways.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

## Trade name Primer HF (Primer SV)

(Contd. of page 6)

Other information: By hydrolysis: methanol and silanol and/or siloxanol compounds.

**12.3 Bioaccumulative potential** No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects: Remark: Harmful to fish

Additional ecological information:

**General notes:** 

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

#### Recommendation

Must be specially treated in compliance with official regulations.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

#### European waste catalogue

07 07 04\* other organic solvents, washing liquids and mother liquors

#### **Uncleaned packaging:**

#### **Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

#### **SECTION 14: Transport information**

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	- Mil
	No

(Contd. on page 8)

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

### Trade name Primer HF (Primer SV)

(Contd. of page 7)

	, , ,	
14.6 Special precautions for user	Warning: Flammable liquids.	
hazard identification number:	30	
EMS Number:	F-E,S-E	
Stowage Category	Α	
14.7 Transport in bulk according to Annex II of		
Marpol and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
,	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
Transport category	3	
Tunnel restriction code	D/E	
IMDG		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
,	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
UN "Model Regulation":	UN 1263 PAINT, 3, III	

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Department issuing data specification sheet: Product Safety department / EHS Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Page 9/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.02.2020 Version number 8 Revision: 03.02.2020

## Trade name Primer HF (Primer SV)

(Contd. of page 8)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3