

Technical Data Sheet Art. No. 6271

Add 250

Wear resistant, transparent, chemical resistant polymer granulate



Protect from
moisture

Range of use

By adding the polymer spheres to liquid sealing materials, transparent as well as coloured, slip resistant sealants can be produced.

Directions

Add 250 is added to the mixed sealant and then mixed until streak-free with suitable mixing equipment.

The ready mixed material is applied according to the instructions given for the sealing material.

Add 250 is only suitable for individual layers < 200 μ thick.

Packaging, application rate, storage

Packaging:

0.25 kg plastic cans

Produktkenndaten

Form:	granulate
Colour:	white
Odour:	odourless
Density:	1.1 g/cm ³ (grain density)

Application rate:

Up to 0.05 kg Add 250 to 1 kg binder

Shelf-life:

Unlimited when stored dry.

Safety, ecology and disposal

Further information on safety for transporting, storage and handling as well as disposal and ecology are found in the latest Technical Data Sheet.

Emergency information:

Mon.-Thurs. from 7:30 a.m. to 4:00 p.m.; Friday from 7:30 a.m. to 2:00 p.m.

Product Safety Department:
Tel.: +49 (0)5432 83-138

After office hours:

Giftinformationszentrum-Nord
[Poison Information Centre North]
24 h hotline +49 (0)551 - 19240

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44 (0) 1293 594 010
Fax: +44 (0) 1293 594 037
www.remmers.co.uk