

# White aluminium oxide grits

SS5001030  
SS5001050

## intended uses

Wear resistant aggregate for the enhancement of slip resistance in Elastadeck™ balcony coating systems. Available in 30 and 50 mesh sizes.

## product description

White aluminium oxide grits.

## product information

**Product reference** SS5001030 – 30 mesh  
SS5001050 – 50 mesh

---

**Theoretical coverage** Varies according to Elastadeck™ system.

---

**Appearance/Colour range** Translucent white particles

## application details

While the Elastadeck™ Walkway Gritcoat is still wet, evenly broadcast White Aluminium Oxide grits onto coated areas.

**Elastadeck™ PB** - 50 mesh at a typical coverage rate of 1kg/m<sup>2</sup>.

**Elastadeck** - 30 mesh at a typical coverage rate range of 1kg/m<sup>2</sup>.

---

**Cleaner** Not required

## storage and handling

**Storage** Store in original packaging in a dry safe place out of the reach of children.

---

**Pack Size/Weight** 25kg

---

**Shelf life** Unlimited if stored dry in unopened packages as above.

## safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

General minimum precautions for all products:

1. Avoid skin and eye contact, i.e. wear gloves, goggles, etc.
2. Ensure good ventilation, mechanical if necessary.
3. Do not eat or smoke in the vicinity of work.
4. Wash hands before eating.
5. Refer to supply container for additional warning labels.

## definitions

### **Tolerances**

All information quoted in this data sheet is subject to normal manufacturing tolerances.

### **Practical coverage**

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

## disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

**Updated March 2018**

**SS5001030/SS5001050**