

Asphalt Easy Fill

A convenient, easy to use crack filler and sealant



Watco Asphalt Easy Fill is a flexible rubberised filler that seals cracks in asphalt, helps protect against damage caused by water ingress and erosion. It can also be used to fill joints and cracks in concrete surfaces. Also bonds to metal, stone and brick. It fits a standard skeleton gun for quick clean repairs.



Areas of use:

- Asphalt
- Concrete
- Stone
- Brick

Features:

- Easy to use
- Flexible, moves with substrate (+/-5%)
- Remains flexible for years
- Protects against damage from water erosion

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Asphalt Easy Fill**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Asphalt Easy Fill

A convenient, easy to use crack filler and sealant

1 Surface Preparation

Ensure that all surfaces are clean, dry and free from any contaminants that may cause adhesion problems.

2 Application

Cut the tip from the cartridge avoiding damage to the thread. Cut the nozzle at an angle of 45° and screw on to the cartridge. The tube fits a standard skeleton gun.

3 Safety

Material Safety Data Sheets are available. In common with all solvent based products, food should be kept away during application and curing.

4 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Asphalt Easy Fill

A convenient, easy to use crack filler and sealant

Specification

Composition	Rubberised black bitumen emulsion.
Appearance	Black.
Number of Components	1
Usage Interior/Exterior	Exterior & interior.
Application Tools	Skeleton gun.
Suitable For	Asphalt, tarmac, metal, stone, brick.
Pack Size	310ml
Coverage	See chart below.
Drying Time	24 hours in dry conditions.
Shelf Life	24 months in unopened container.
Storage	Store in shaded dry conditions between 5°C - 25°C. Do not allow to freeze.
Principle Limitations	Not suitable for use on EPDM rubber roofs. Check compatibility with other surfaces if in doubt.
Please contact us regarding applications not described here.	

Coverage Rates

Linear metres per 310ml cartridge.

Width (mm)	6	10	15	20	25
6mm deep	8.6	5.3	3.4	2.6	2.1
10mm deep	5.2	3.1	2.0	1.5	1.2
12mm deep	4.3	2.6	1.7	1.3	1.0