

Bitu-Mend[®] Deep Fill

Repairs deep holes in asphalt and concrete



Watco Bitu-Mend[®] Deep Fill is ideal for filling deep holes (up to 200mm) in asphalt and concrete, without the need to make up the repair in layers. The epoxy resin formulation provides high strength throughout the depth of the repair making it ideal for heavily trafficked areas.



Areas of use:

- Deep holes in heavily trafficked areas like car parks or loading bays
- Tarmac and Asphalt

Features:

- Cures to a hard, black, slip resistant finish
- No primer required
- Can be applied at any thickness from 15mm - 200mm
- Suitable for use inside and out
- Ready for use in 12 hours

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Bitu-Mend[®] Deep Fill**.

Call our expert team on: 01483 418 418 (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Bitu-Mend[®] Deep Fill

Repairs deep holes in asphalt and concrete

1 Surface Preparation

Ensure the void to be filled is clean, dry (slight damp is acceptable) and sound. Prime surfaces with Watco Tack Coat.

2 Mixing

Mixing is easier on a board, but it can be done in the plastic container provided. Empty the contents of the smaller Curing Agent tin into the larger Resin tin and mix thoroughly using a palette knife or similar wide bladed tool. Immediately empty the mixed components onto the granite aggregate. Mix using a trowel to achieve a loose textured black compound. Ensure that the dry aggregate is thoroughly coated.

3 Application

Tip the mixed product into the void and work into any gaps and crevices with a trowel. Lightly tamp down with a piece of wood; compacting the product to remove air pockets. Finish with a trowel wiped with white spirit for a smooth finish.

4 Safety

All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.

5 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Bitu-Mend[®] Deep Fill

Repairs deep holes in asphalt and concrete

Specification

Composition	A blend of graded granite aggregate and epoxy resin.
Finish	Granular, black, slip resistant surface.
Primer Required	A primer is not required when filling rough holes or cracks. We recommend Watco Tack Coat primer if using Watco Bitu-Mend [®] Deep Fill over smooth substrates.
Number of Components	1 x resin, 1 x curing agent, aggregate.
Usage Interior/ Exterior	Exterior & interior.
Application Tools	Trowel.
Suitable For	Asphalt, tarmac.
Pack Size	25kg
Coverage	The volume of a 25kg pack is approximately 15 litres. As a guide this would cover 0.5m ² at 30mm thick.
Chemical Resistance	Good general resistance to many chemicals commonly found in industry. Please contact us for advice regarding other chemicals.
Curing Time	Can be walked on after 8-12 hours and subject to heavy traffic after 12-24 hours (all at 10°C - 20°C). Lower temperatures will extend the curing time.
Pot Life	Working life of mixed components: 30 minutes at 10°C - 20°C, less in higher temperatures.
Shelf Life	12 months in unopened container.
Storage	Store above 10°C. Do not allow to freeze.