

Bitu-Mend®

An easy-to-use material for repairing potholes




Rapid repair for potholes in Asphalt and Concrete. Watco Bitu-Mend® is a durable bitumen-based patch repair for use on exterior pot-holed asphalt and concrete. Repairs with Watco Bitu-Mend® are ready for instant trafficking.

Watco Bitu-Mend® is applied as a soft, flexible material which gradually hardens over time following application. The repair can be instantly trafficked by cars. For very heavy traffic areas or areas where forklift trucks are used, please use Bitu-Mend® Advanced.



Colours



Black

Samples are available on request. While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

Areas of use:

- Ideal for pot-holes in roadways, vehicle parks, loading docks, paths, airfields etc.
- Asphalt, Tarmac and Concrete repairs

Features:

- Compacts to a dense hard surface that will resist vehicle and pedestrian traffic.
- Repairs can be driven over immediately
- Easy to use
- Withstands heavy traffic
- Includes easy to use primer
- Suitable for holes between 10mm and 75mm deep

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Bitu-Mend**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Bitu-Mend[®]

An easy to use material for repairing potholes

1 Surface Preparation

Remove all loose material and surface water, oil etc.

2 Application

Pour the primer onto the prepared surface and spread using a brush. Tip or shovel out sufficient material into the hole to slightly overfill it and then compact with the back of a shovel or tamper.

3 Safety

Material Safety Data Sheets are available.

4 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Bitu-Mend[®]

An easy to use material for repairing potholes

Specification

Composition	Polished aggregate together with liquid binder based on bitumen plus resins and adhesives.
Number of Components	1 x Primer 1 x Watco Bitu-Mend
Colour	Black.
Usage Interior/Exterior	Interior & exterior.
Application Tools	Hand shovel, tamper.
Suitable For	Concrete, sand & cement, asphalt.
Pack Size	25kg
Coverage	0.5m ² at 25mm thick. Watco Bitu-Mend [®] can be applied at up to 75mm thick.
Curing Time	The repair may be driven over immediately and the product will harden over time following application.
Shelf Life	24 months in unopened containers.
Storage	Re-fit container lid tightly after use. Store in a warm location. Do not allow to freeze.
Safety.	All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.