



## Color SA plus

High quality, low-emission interior wall paint with micro-silver as a film preservative for protection against fungal attack



Colour	Availability		
	Quantity per pallet	48	32
	Packaging unit	5 l	12,5 l
	Type of container	Plastic bucket	Plastic bucket
	Container code	05	13
	<b>Art. no.</b>		
white	2984	■	■
special colours	2986	■	■
Can be adjusted based on RAL, NCS etc. upon consultation			

### Application rate

Approx. 0.15 l/m<sup>2</sup> per coat (depending on the substrate properties).

Apply to a large enough trial area to determine the precise amount required.



### Range of use



- Surfaces at risk of mould, e.g. in living rooms, schools, nurseries, offices, hotels, restaurants, wellness facilities
- Finishing coat on mineral wall formers, renders, gypsum plasterboard, raw fibre and fibreglass wallpaper, adhering old coatings
- In areas for people sensitive to mould (children, people with allergies)

### Property profile



- Water vapour diffusion capable
- Hard-wearing and resistant to scrubbing (wet abrasion class 2 as per DIN EN 13300)
- Good hiding power (class 2 as per DIN EN 13300)
- Gloss level: matt
- Free from solvents and plasticizers

### Characteristic data of the product

#### ■ On delivery

Binder	Pure acrylate binder
Density (20 °C)	Approx. 1.15 kg/l
Viscosity	Suitable for application



■ **Once fully cured**

Colour	White
Degree of gloss	Dull matt

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

**Certificates**

- [Technical guidelines: mould remediation](#)
- [Examination report: fungal attack](#)
- [Examination report: bacterial attack](#)
- [Indicative test report 2010-1049 Exova](#)
- [Test report 1-120-09 wet abrasion resistance DIN EN 13300](#)
- [Test report iLF determination of heavy metal content DIN EN 71-3](#)

**Possible system products**

- [Hydro Deep Primer \(0725\)](#)

**Preparation**

■ **Substrate requirements**

Dry, clean, free of dust and cracks (except hairline cracks) and capable of supporting a load.


Structural deficiencies such as heat bridges must be eliminated.

Condensation must be avoided.

■ **Substrate preparation**

Completely remove any superficial mould infestation using Remmers Mould Stop\*.

**Directions**



■ **Conditions for use**

Temperature of the material, air and substrate: from min. +8 °C to max. +25 °C

Stir well.

Coat the surface using a suitable tool.

Apply the material in 2 coats, depending on the condition of the substrate.

Wait at least 8 hours between coats.

**Tips on use**

Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.

The first coat can be diluted with up to 5% water.

**Notes**

Deviations from applicable regulations must be agreed separately.

The relevant test certificates must be observed when planning and carrying out work.

Always set up a trial area/trial areas first.

**Tools / Cleaning**




Brush, surface brush, lamb's wool roller, ceiling brush

Clean tools with water while the material is still fresh.

Clean splashed material with water while the material is still fresh.

**Storage / Shelf life**



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 6 months.

**Safety data / Regulations**



For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

**Disposal** Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

**Biocidal Products Regulation** Contains as "treated goods" a biocidal product (film preservative) with the biocidal active agent silver phosphate glass to protect the film from contamination by microbial organisms (algae, mould etc.). Always follow the directions carefully!

**VOC content as per the "Decopaint" Directive (2004/42/EC)** EU limit value for the product (Cat. A/a): max. 30 g/l (2010). This product contains < 30 g/l.

VOC	
Kat.	A/a
2010:	30g/l
max.:	30g/l

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.