

GRP Decking Strips

Easy-to fit strips make slippery decking instantly safer



Wooden decking and ramps can be hazardous in the wet or become slippery with algae in shady or damp conditions. Damp, slippery timber can be made safer instantly using Watco GRP Decking Strips. Glass Reinforced Plastic (GRP) strips come in two textures, medium and extra coarse, bringing security underfoot on unprotected decks. Watco GRP Decking Strips are suitable for use in both commercial and domestic areas and are especially effective in wet conditions. Holes are pre drilled at approximately 300mm intervals. One row of holes is drilled in the 50mm and 90mm wide strips, two rows in the 120mm width. Holes are 50mm in from each end. Screws are supplied for fixing to timber. Medium Grade Decking Strips are supplied in 1200mm and 2400mm lengths and 50mm or 90mm widths. They are designed for areas of decking mainly used by children or vulnerable adults.

Areas of use:


- Wooden decking
- Walkways
- Jetties, pontoons and marine slipways
- Bridges

Features:

- Waterproof, rotproof and will not warp
- Easy fit, all items preformed. Glue or screw fix, pre-drilled for easy fixing to timber and with all screws supplied
- Child friendly. Medium coarse option perfect for decks used by children or vulnerable adults
- Suitable for domestic and commercial decking (unsuitable for barefoot areas)
- Excellent slip resistance even in the wet
- Oil and chemical resistant
- Cut to size service available with no charge or can be trimmed on site using a hacksaw if required
- Ideal for wet or weak substrates which cannot be adequately prepared for paint
- Chamfered edges minimise trip hazards
- Helps meet the requirements of the DDA and 2004 Building Regulations



Colours



*Samples are available on request.

While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **GRP Decking Strips**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



GRP Decking Strips

Easy-to fit strips make slippery decking instantly safer

Specification

Dimensions for Medium Grade Strips	1200mm x 50 & 90mm. 2400mm x 50 & 90mm.
Dimensions for Coarse Grade strips	1200mm x 50, 90 & 120mm. 2400mm x 50, 90 & 120mm.
Primer required	No.
Suitable for	Wood
Usage Interior/Exterior	Exterior.
Grades	Medium & Coarse.
Pack size	Packs of 10.
Cut to size service	Yes.
Oil & chemical resistant	Yes.
Lightweight	Yes.
Non sparking	Yes.
Non metallic	Yes
Fixing	Just lay the strip onto the wooden decking and fix using an appropriate screw. When drilling the strip it is not necessary to countersink the hole.

Grades & Slip resistance



Watco GRP Decking Strips are available in 2 grades



Medium Grade
Low slip potential
Wet PTV 71



Extra Coarse Grade
Extremely low slip potential
Wet PTV 80



The UK Slip Resistance Group guide to slip resistance of a floor for able bodied pedestrians:

Four S Pendulum Value	Potential for Slip
Above 65	Extremely Low
35 to 65	Low
25 to 35	Moderate
25 and Below	High

Slip resistance levels measured using the Pendulum Test method (WF rubber slider) – certificate available on request.
To ensure that the above slip resistant levels are maintained the strips should be kept clean.