

Watco GRP Ladder Rungs

Makes slippery ladder rungs safe even when wet or oily



Avoid accidents when working at height with Watco GRP Ladder Rungs. Watco GRP Ladders Rungs are formed with 4mm thick fibreglass with a gritted surface, to provide good grip, even if the ladder becomes wet or oily.

We recommend fixing into place using our high strength GRP Polyurethane Adhesive fitted into a skeleton gun. A 295ml tube of adhesive should be sufficient for approximately 10 rungs. Avoid application during wet or cold conditions.



Colours



Samples are available on request. While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

Areas of use:

- Wood, metal or aluminium ladders to improve grip for hands and feet

Features:

- Available in a wide variety of sizes to suit most ladders
- Can be cut to size
- Fix into place with our high strength GRP Polyurethane Adhesive (fits a standard skeleton gun)
- Low slip potential - Wet PTV 60

Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Watco GRP Ladder Rungs**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Watco GRP Ladder Rungs

Makes slippery ladder rungs safe
even when wet or oily

1 Surface Preparation

If you need to cut the GRP product, a good quality abrasive disc, jigsaw or hacksaw can be used. The GRP material is quite tough to cut by hand, so if power tools are not readily available, please ask about our cut to size service.

Ladder rungs should be clean and dry.

Remove any loose paint and wipe surfaces with a solvent based cleaner (eg. white spirit) to remove any grease.

Remove any dust from the inside of the Watco GRP Ladder Rung.

2 Application

Lay the items in place to ensure that they fit. Trim using a jigsaw with medium cutting blades (Bosch TI01 AIF or similar are ideal).

Fix in place with Watco Polyurethane Adhesive, ensuring the surface is suitably clean and dry beforehand.

Cut approximately 35mm from the end of the nozzle of the GRP Polyurethane adhesive, (a sufficient amount of the nozzle should be cut off to provide a 10mm bead of adhesive).

Apply a 10mm bead of adhesive to the inside middle of each Watco GRP Ladder Rung (do not apply to more than 5 rungs at a time).

Starting with the top ladder rung, place a Watco GRP Ladder Rung over it and while swivelling it back and forth apply a downward pressure until the adhesive oozes out of each end. Remove any excess adhesive.

Avoid using the ladder for a minimum of 24 hours.

Specification

Composition 4mm thick fibreglass.

Number of Components 1

Usage Interior/ Exterior Interior & exterior.

Application Tools Skeleton Gun.

Suitable For Metal, wood or aluminium.

Size 25mm or 38mm internal dimensions by 300mm lengths. Can be cut to size.

Dry film thickness 25mm

Cut to size service Yes

Pendulum Dry PTV: 65 - Low slip potential.

Slip Test Values Wet PTV: 60 - Low slip potential.

Fixing See surface preparation and application.