

# Weatherguard

A tough, flexible and long term decorative coating for walls



Watco Weatherguard is formulated to give an impermeable protective coating that will withstand extreme temperature without softening or hardening. Extremely tough and flexible, it can be applied to almost all surfaces. The cured film will stretch up to twice its original surface area without detrimental effect and will cope with any movement caused by temperature change, settlement or flexing. Controlled vapour permeability minimises build-up of condensation and loss of film adhesion.

Watco Weatherguard will reduce solar heat gain as it will reflect 85% of infra-red radiation.




**Areas of use:**

- Ideal for previously untreated concrete and masonry surfaces
- Use on floors and walls in factories, warehouses and machine shops
- Suitable for treating cement screeds, porous tiles, brickwork, blockwork and plaster

**Features:**

- Weatherproofs and protects exposed or painted masonry
- Life expectancy of at least 10 years
- Weather and waterproof
- Impact resistant
- Allows for considerable surface movement
- Will not support fungal or algae growth

**Colours**



Samples are available on request.

While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

## Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Weatherguard**.

**Call our expert team on: 01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



# Weatherguard

A tough, flexible and long term decorative coating for walls

## 1 Surface Preparation

The surface to which Watco Weatherguard is to be applied should be clean, dry and free of any loose material and contamination. Use a fungicide to remove any fungi, mildew or moss, etc. Scrape off any loose paint. Existing hard smooth, glossy paint should be lightly sanded to provide a key. Wash with a detergent solution, rinse with water and allow to dry. Make good any minor defects with an external filler or sand/cement mix.

**Wooden Surfaces** – All bare wooden surfaces should be clean and dry. Do not apply to door or window frames or previously painted wood unless all traces of old paint have been removed.

## 2 Stirring

Blend in (do not stir) any thin liquid that may have appeared on the surface of the product.

## 3 Application

Apply Watco Weatherguard by brush or roller in one direction at the rate of 4m<sup>2</sup> per litre, allowing the first coat to dry before applying the second coat in the opposite direction.

## 4 Safety

All product labels provide general safety information. Material Safety Data Sheets are available.

## 5 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

# Weatherguard

A tough, flexible and long term decorative coating for walls

## Specification

<b>Composition</b>	Water based acrylic polymer.
<b>Number of Components</b>	1
<b>Finish</b>	Matt or low sheen depending on substrate.
<b>Primer Required</b>	No.
<b>Number of Coats</b>	1
<b>Usage Interior/Exterior</b>	Exterior.
<b>Application Tools</b>	Medium pile roller or brush.
<b>Suitable For</b>	Brick, masonry, stone, rendered and other cementitious surfaces.
<b>Pack Size</b>	10L
<b>Coverage</b>	Generally 40m <sup>2</sup> per 10L per coat depending on the substrate.
<b>Drying Time (For Overcoating)</b>	Touch dry: 4 - 6 hours at 20°C. Lower temperatures or damp humid conditions will extend the drying time.
<b>Cleaning Tools</b>	Wash brushes or rollers with water immediately after use.
<b>Shelf Life</b>	24 months in unopened container.
<b>Storage</b>	Protect from frost. Do not allow to freeze.
<b>Safety</b>	Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.
<b>Storage</b>	Protect from frost. Do not allow to freeze.
<b>Principle Limitations</b> Please contact us regarding applications not described here	Do not apply in damp, humid conditions or if rain is forecast within 24 hours. Only apply at temperatures above 5°C.