



Quartz 20/30

Natürliches Quarz-Aggregat zum Verblenden über Epoxid-Grundierungen

Type/Name	Availability
	Quantity per pallet
	Packaging unit 25 kg
	Type of container Paper bag
	Container code 25
	Art. no.
2 -3 mm	260017 ■

Application rate Abhängig von der Anwendung

Range of use ■ Einstreusand in Remmers-Systemen

Property profile

- Gewaschen
- Ofen getrocknet
- Staubfrei

Characteristic data of the product	Korndichte	1.47 g/cm ³
	Form	Rounded
	Körnung	Approx. 2 - 3 mm

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.


Application examples ■ **Einstreumaterial**
Vollsatt und gleichmäßig im Überschuss in die geeignete, noch frische Remmers-Beschichtung einstreuen.
Nach Erhärten den nicht eingebundenen Überschuss entfernen.

Notes Der max. Füllgrad ist abhängig von dem verwendeten Bindemittel, der Schichtdicke und den Baustellengegebenheiten.
Weitere Hinweise zu Verarbeitung, Systemaufbauten und Pflege der aufgeführten Produkte sind den jeweiligen aktuellen Technischen Merkblättern und den Remmers Systemempfehlungen zu entnehmen.



Storage / Shelf life

Bei trockener Lagerung unbegrenzt.



Safety data / Regulations

Nähere Informationen zur Sicherheit bei Transport, Lagerung und Umgang sowie zur Entsorgung und Ökologie sind dem aktuellen Sicherheitsdatenblatt zu entnehmen.

Disposal

Entsorgung gemäß den behördlichen Vorschriften.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.