

Torstrip WDA10 Wash Down Agent

SS4200005

intended uses

For the washing down of previously painted surfaces prior to application of paint systems.

For the washing down recently stripped surfaces prior to application of paint systems.

product description

A blend of surfactants, detergents and water.

product information

Product reference SS4200005

Theoretical coverage N/A

Practical coverage N/A

Appearance/Colour range Clear

VOC content 0 grams/litre

application details

Method of application Dilute with water, 1 part Torstrip WDA10 to 10 parts water.

Apply by brush or cloth.

storage and handling

Storage Store in a safe place out of the reach of children

Pack Size 5 and 25 litres

Flash point Non flammable

Product weight 1.1kilogram/litre

Shelf life 1 year

surface preparation

Previously painted: Prepare by removing all defective paint back to a solid edge. Repair with a high quality surface filler if necessary. Spot prime filled or bare areas. Remove existing graffiti using Torclean Graffiti Remover Wipe System SS456 or Torclean 'G' Graffiti Remover DM424. Make good any damaged surfaces.

Stripped: To be applied following application of Torstrip VSA20 Multi-Layer Paint Stripper, Torstrip HSA20 Multi-Layer Paint Stripper or Torstrip WBS Multi-Layer Paint Stripper.

limitations

Rinse off thoroughly with water.

safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

A draft Torstrip Method Statement is available and recommended for use.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc.
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

definitions

Tolerances

All information quoted in this data sheet is subject to normal manufacturing tolerances.

Practical coverage

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

Pot Life

Applies only to two pack products and refers to the time the mixture remains usable.

VOC

Volatile organic compounds

dft

Dry film thickness

wft

Wet film thickness

disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

**Updated: September 2010
SS420005**